

# Model 1510

## Single Point Load Cells

NEW!



### Features

- Capacities: 100, 250, 500 kg
- Stainless Steel Construction
- Single Point 600x600mm Platform
- 6 wire (sense) circuit
- Fully welded, providing IP68 Protection
- OIML R60 approved
- Hazardous area approved to Eex ia IIC T6

Model 1510 is a high accuracy single point load cell ideally suited to industrial applications which undergo regular wash down, typically platforms, wall scales and other process weighing application in the food industry.

Hermetically sealed against moisture, the all welded construction of the model 1510 in combination with a polyurethane dual shielded cable, enables continuous operation in harsh environments whilst maintaining a high operating specification.

The two additional sense wires feed back the voltage reaching the load cell. Complete compensation of changes in lead resistance due to temperature change and/or cable extension, is achieved by feeding this voltage into the appropriate electronics.



EXCELLENCE IN LOAD CELLS

#### Contact Info

E-mail  
sales@tedea-huntleigh.com  
Website  
www.tedea-huntleigh.com

**Europe**  
Tedea-Huntleigh  
Europe Ltd.  
37 Portmanmoor  
Road  
Cardiff  
CF24 SHE

**International**  
Tedea-Huntleigh Inter-  
national Ltd.  
5 Hozoran St.  
New Industrial Zone  
P.O. Box 8381, Netanya  
42506

**China**  
Beijing Tedea-Huntleigh  
No. 16 Hong Da Bei Lu  
Da Xing County, Beijing  
Economic & Technology  
Development Area,  
Beijing 100176  
Tel:+86-10-67881604-

**Germany**  
Tedea-Huntleigh  
GmbH.  
Mumlingweg 18  
D-64297  
Darmstadt-  
Eberstadt

**France**  
SEEA sa  
16 Rue Francis  
Vovelle  
28000 Chartres  
France

20630 PLUMMER ST  
CHATSWORTH CA 91311  
USA

TEL: 800.626.2616  
FAX: 818.701.2799

# Model 1510

# Single Point Load Cells

Grade	E	C3**	Units
Rated Capacities	100, 250, 500		kg
Rated Output	2.0 ± 10%		mV/V
Total Error*	0.03	0.02	±% of Rated Output
Zero return after 30 mins	0.05	0.017	±% of Applied Load
Temperature Effect: On Output	0.003	0.0011	+-% of Applied Load/°C
Temperature Effect: On Zero	0.01	0.0023	±% of Rated Output/°C
Eccentric Loading	0.005	0.0016	±% of Applied Load/cm
Zero Balance	10		±% of Rated Output
Temperature Range: Operating	-30 to +80		°C
Temperature Range: Compensated	-10 to +40		°C
Safe Overload	150		% of Rated Capacity
Ultimate Overload	200		% of Rated Capacity
Excitation: Recommended	10		Volts AC or DC
Excitation: Maximum	15		Volts AC or DC
Input Impedance	380±10		Ohms
Output Impedance	350±3		Ohms
Insulation Impedance	>1000		Mega Ohms
Deflection at Rated Capacity	<0.4		mm
Weight: (including cable)	2.4		kg
Construction	Stainless Steel		
Environmental Protection	IP68		
Cable	3 Meter (Standard), 6 Wire, Polyurethane Jacket, Dual Floating Screen		

\*Total Error—According to OIML R60    \*\*Standard utilization 50%, alternative utilization options down to 25%    C4 Grade Available

### Outline Dimensions All Capacities (in mm)

